

CR-DIGW0921WB

900MHz/2100MHz Dual-band

Key Features

- Dual band for 900MHz/2100MHz antenna-sharing systems
- A wide range of products with various output power
- Higher, lower requirement for input signals
- High linear PA
- Gain is adjustable, which enables more flexible applications
- LED indicator for convenient observing equipment operation status
- ALC function to stable coverage effect
- Low power consumption, low interference



Specifications

ELECTRICAL

Frequency	UL:890-915MHz & 1920-1980MHz DL:935-960MHz & 2110-2170MHz		
Output Power	DL:20±2dBm UL:15±2dBm	DL:24±2dBm UL:20±2dBm	DL:27±2dBm UL:24±2dBm
Gain	DL: 70±2dB UL: 65±2dB	DL:75±2dB UL:70±2dB	DL:80±2dB UL:75±2dB
Gain Adjust Range	≥30dB; 1dB/step		
AGC Range	≥20dB		
Noise Figure	≤8dB		
Ripple in Band	900MHz≤8dB; 2100MHz≤6dB		
Time Delay	≤1.5μs		
Intermodulation	9-1GHz	UL≤-36dBm@ 3KHz DL≤-20dBm@ 3KHz	
	1-12.75GHz	UL≤-30dBm@ 3KHz DL≤-20dBm@ 3KHz	
Spurious Emission	9-1GHz	≤-36dBm@ 3KHz	
	1-12.75GHz	≤-30dBm@ 3KHz	
VSWR	≤2.0		
Port Impedance	50Ω		

POWER, MECHANICAL & ENVIRONMENTAL

Weight	<2.5 kg
Dimension	250×145×53 mm
Installation Mode	Wall installation (Normal)
RF Connection	N Female
Power Consumption	<25 W (24dBm & 27dBm < 35W)
Power Supply	AC90—240V/DC 12V/3A
Temperature	-10~+50℃
Chassis	IP40 Metal